


THERMISER MAX[®]

Model ESD30

MEASURE THE WIDTH AND HEIGHT OF THE OPENING

DOOR SIZE AND AREA




COMPONENT DIMENSIONS

Reference the zone number to view component dimensions for motorized doors.

Dimensions in Inches

1	17	19	5	9
2	18	20	5	9
3	19	21	5	9
4	20	22	7	9
5	21	23	7	11
6	22	24	7	11
7	23	25	7	11
8	24	26	7	11
9	25	27	7	11
10	26	28	7	11
11	27	29	7	11
12	29	31	7	11
13	31	33	7	11

Zone A B C D



The dimensions featured on this sheet are provided as a guide. Please visit our website at www.cornelldoor.com/drawings to generate drawings on demand with exact dimensions.

Sound Transmission Class (STC) ratings are available for a variety of Themiser Max door configurations. *If an STC of 32 is desired, additional options are required. Please contact the factory for details. All configurations are evaluated per ASTM E90, based on testing a complete operable assembly.


Gauge	STC Rating
22/22 or 18/24	27
18/24	30
18/24	32*

INSULATED ROLLING DOOR **THERMISER MAX® Model ESD30**

GUIDE CONSTRUCTION OPTIONS


FACE OF WALL Z

Typically used with masonry wall construction, guides are mounted to the interior side of the wall.




FACE OF WALL E

Typically used with steel jambs, guides are mounted to the interior side of the wall.




BETWEEN JAMBS

Used when side clearance is minimal, guides are mounted to the inside of the jamb.




CURTAIN DESIGN


Insulated Slat



LINTEL SEAL BRUSH



FOAM BLOCK



Air Infiltration value of less than .3 CFM/FT².

R Value of 8.0

U Value of .125

Calculated using the ASHRAE Handbook of Fundamentals

The dimensions featured on this sheet are provided as a guide. Please visit our website at www.cornelliron.com/drawings to generate drawings on demand with exact dimensions.

CUSTOM-DESIGNED SOLUTIONS

Our experienced Architectural Design Support Team can customize our products to fit your specific application.

Call 800.233.8366 ext. 4551 • architecturalsupport@cornellcookson.com

800.233.8366 | cornelliron.com

CornellCookson, Inc. is an ISO 9001:2015 registered company
9.2022

CORNELL
Innovative door solutions.